



GLOBAL TEC TRADE SRL



DETAILS

LIGHT SOURCE T15M/ TLS-25

FEATURES:

- Pocket size design
- Highly accurate unit offering 6 calibrated wavelengths
- Interchangeable connectors
- Durable and reliable design
- Easy-to-use interface for error-free testing
- Rubber armor protection

Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Optical Light Source

Work with T25m Optical Power Meter

T15m



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Product Features



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Ergonomic Design



One-handed Operation

light source

180 g **135*60 mm**
Weight Dimension



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Modulation Carrier Output

light source

Continuous output, three modulation frequencies

270Hz/1000Hz/2000Hz



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Removable Silicone Protective Case

Shock-proof Drop-proof

light source



Split design

Reduce collision, enhanced toughness



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

LED Lighting

light source

The equipment can work stably
in the dark and improve efficiency



☀ LED Lighting could be turned on and off at will

Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

2.5mm Universal Connector+SC Adapter

light source



FC



ST



SC



Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Multiple Wavelength Available Water-resistant Keys

light source



λ

1310/1550nm optional



CW/Hz

Modulate carrier,
three frequencies available:
270Hz/1000Hz/2000Hz



LED

Turn on/off the LED Lighting



Power

One-key start,
long press trun-off

Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Specification



Model	T15M
Wavelength	1310+1550nm
Typical Output Power	-5dB
Optical Connector	SC+2.5mm universal (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(2 AAA 1.5V batteries)
Output Stability	$\pm 0.05\text{dB}/15\text{mins}$; $\pm 0.1\text{dB}/8\text{hours}$
Modulation Frequencies	CW, 270Hz, 1KHz, 2KHz
Dimensions / Weight	130*65*35(mm)/180g
Silicone protective case	Yes

Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL

Product List

T15M



- 1.Packing Box 2.Optical Light Source 3.Certificate of Conformity
4.Warranty Card 5.User Guide 6.Battery 7.SC Connector

Tel. 11-2300-3000

info@gtt.com.ar

www.gtt.com.ar