



GLOBAL TEC TRADE SRL



11-2300-3000

OPTICAL POWER METER OT200-8



Características:

- Iluminación LED
- Apagado automatico
- Interruptor de retroalimentación
- Función de memoria de longitud de onda
- Calibración de usuario
- Visualización simultanea de mW lineal e índice no lineal dBm
- Interfaz universal de 2,5mm, interfaz SC FC ST

Superi 4430, CABA (1430)

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL



11-2300-3000

- Fuente de alimentación externa como tesoro de carga, computadora, etc

ESPECIFICACIONES:

	OPM	
Wavelength range	800 ~1700nm	
Optical detector	InGaAs	
Interface type	2.5 Universal Connector	
Power measurement range	-70~+6dBm	-50~+26dBm
Uncertainty	±5%	
Standard wavelength	850/1270/1300/1490/1550/1577/1625nm	
Display resolution	Log display: 0.01dBm	
Recognizable frequency	270Hz 1Hz 2KHz	
	VFL	
Operating wavelength	650nm	
Output power	15mW	
Working mode	CW/2Hz	
Interface type	2.5 Universal Connector	
	RJ45 Sequence	
Test mode	Test the sequence of network cables	
	Other	
Power Supply	2 AAA bateries/Optional lithium batteries, 3.7V/800mAh	
Port	Type C	
Automatic shutdown time	10min	
Operating temperature	-10C~+50C	
Storage temperature	-40C~+70C	
Relative temperature	0~95%RH	
Dimension	110*68*30mm	
Weight	140g	

Superi 4430, CABA (1430)

info@gtt.com.ar

www.gtt.com.ar