



GLOBAL TEC TRADE SRL



11-2300-3000

SW-102 UV 125-525MHz

V.S.W.R. meter Introduction

VSWR. Forward and reflected power direct digital readout, without any calibration.

Maximum measurable power range up to 120W.

low insertion loss (0.3 decibels or less) structure allows it to be permanently connected.

Build in Frequency counter (SW102UV only) .

All Function display (SWR,FW,RW,Battery Level)



Feature & Specification

Frequency range: 125 - 525MHz

Measurable power range: 0.5 - 120W(+/-0.5%)

Measurable S.W.R range: 1.00:1~19.99:1

Input read frequency counter (must be < 0.5 W)

Maximum power: 120W

Impedance: 50Ω

Size: W 76 X H 77 X D35 mm.

Weight: < 220 grams

Battery : 3.7V Li-ion Rechargeable Battery

Superi 4430, CABA (1430)

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL



11-2300-3000



Cautions : SW-102 Error Display (show 229.9W)

* DMR INPUT

*Frequency out of 100-525MHz

*Input level below 0.3 w

*Input up to 120 Watt



Superi 4430, CABA (1430)

info@gtt.com.ar

www.gtt.com.ar



GLOBAL TEC TRADE SRL



11-2300-3000



Interface: N-J Interface/ SO239

MAX. Power in :120 W (Measurable power, Radio must be ANALOG)

V.S.W.R1.00 :1 ~ 19.99:1

Frequency Range COVER : 125MHz~525MHz SW102UV

Insertion Loss< 0.15dB(VHF) , < 0.25dB(UHF)

Temperature 0°C~60°C

Frequency counter : SW102UV only (TX input must be minimum 0.5W + - 0.5%)

Battery Level Display : Yes

Battery Build-in :3.7V Li-ion Battery

Auto Power Off : 1-9 mins

Size: 66*68*37 (mm)

Charger in 5V (micro usb)

Back-light AUTO OFF

Interface (in and out)N / SO239 (SL16)

Weight: 220g (include battery)

Superi 4430, CABA (1430)

info@gtt.com.ar

www.gtt.com.ar